

2 Belt Fully Automatic Side Sealer

Model:

INT-20

Versatile machine capable of running a wide variety of industrial or consumer products.



“APA”
Automatic Product
Adjustment



7" Color Touch-Screen with
20 Presets and Self Diagnostics

“APA” machine automatically adjusts
inverting head and infeed conveyor to
different package sizes from one touch
control panel in less than 15 seconds!




“APA” Automatic Product Size
Adjustment of Inverting Triangle &
Infeed Conveyor *Exclusive Feature!

Versatile ★ Dependable ★ Affordable

The model **INT-20 2 Belt Side Sealer** features “**State of the Art**” technology. Includes Delta PLC with 7” color touch screen control panel, 20 program memory, multiple languages, cycle speeds of up to 40 ppm, 20” cross seal head design for greater flexibility and taller packages. No maintenance side seal wheels, will seal polyolefin and polyethylene films. Exclusive “**APA**” **Automatic Product Adjustment**, eliminates all crank handles and features programed motorized adjustments of the infeed conveyor and inverting head, making product changeovers simple, fast and accurate. Variable speed drive 0-95 fpm, front load film mount, pin wheel hole punch, **self diagnostic color touch screen**, and self-contained scrap removal system with built-in alarm, are just a few features that make this machine the best in the industry.

Reliability, simplicity and ease of maintenance should provide years of dependable performance at low operational cost. The **INT-20 2 Belt Side Sealer** is an extremely versatile machine capable of running a wide variety of industrial or consumer products. The **INT-20 2 Belt Side Sealer** features a **Motorized Center Seal** that allows for precise seam placement and taller package heights.


2 Belt Fully Automatic Side Sealing Machine




Touch Screen Automatically Adjusts Side Seal, Inverting Head and Infeed Conveyor



Optional 3' or 6' flighted or belted infeed conveyor



Front Load Film Cradle with Pin Perf Wheels, Saves Space



Maintenance-Free Side Seal Seals Virtually All Films

Available Options:

- Pneumatic Hole Punch
- 3' Flighted Infeed
- 6' Flighted Infeed
- Belted Conveyors
- Programable Side Seal
- Flight Bar Conveyors
- Closing Conveyor
- Print Registration
- Stainless Steel Frame

Model	INT-20 2 Belt	INT-30 2 Belt
Seal Area	20" Cross Seal x 8"H	30" Cross Seal x 10"H
Machine Speed	Up to 40 PPM	Up to 40 PPM
Electrical	220V, 1 Phase, 20 AMP	220V, 1 Phase, 20 AMP
Air	1CFM @ 80 PSI	1CFM @ 80 PSI
Minimum Pkg Size	2.5"W x 3"L	3"W x 4"L
Maximum Pkg Size *	Inf. L x 16"W x 6"H	Inf. L x 26"W x 8"H
Maximum Film Width	24"	35"
Machine Dimensions	73"L x 49"W x 67"H	114"L x 65"W x 70"H
Shipping Weight	1,500 lbs	2,500 lbs
Warranty	1 year	1 year

*Maximum dimensions may not be combined.

