Top Applicator with Stand

Model:

PP-601

A fast, simple solution for labeling the tops of products



♦ EASY TO USE

The Delta HMI interface makes it easy to use the PP-601. Simple hand wheel adjustments make for quick set-up and fast changeover time keeping the machine online with less downtime.

♦ LOW MAINTENANCE

Manufactured to (GMP) standards, the PP-601 is made of #304 stainless steel and anodized aluminum, and designed to be used in harsh working environments where other equipment might fail. The Preferred Pack® machine is the right choice for the discriminating buyer.

♦ SIMPLE DESIGN

Built into all Preferred Pack® designed labeling machines is a cost effective solution to fast, reliable, pressure-sensitive top labeling for trays, boxes, chipboard containers, bags and even caps on bottles.



PERFORMANCE

- The preset counter means the machine automatically stops once the preset quantity of products has been labeled.
- The product counter lets you precisely track the amount of labels applied at any point during the production run.
- The PP-601 feature a Delta PLC Touchscreen HMI control system that maintains default settings and memory locations.

EFFICIENT

- The digital label adjust position allows the operator to set the desired position of the label to the package with just one touch.
- The missing label feature locates missing labels on the roll stock, and shuts the machine down if one is found. This ensures each product is labeled correctly.

ADJUSTABLE

- The standard Delta Touchscreen HMI with 83 program memory and label sensors can be easily adjusted for a wide variety of labeling applications. With the digital position setting, your labels are placed accurately on the product every time.
- The PP-601 offers an optional hot-stamp ribbon printer which can easily be installed should the need arise.
 This optional feature lets printers work in sync with the labeler to ensure accurate code placement.
- Designed to be used for in-line automatic or semiautomatic applications.

SENSIBLE

- The PP-601 come with casters and can be conveniently moved to other production areas, allowing for changes in production or products.
- All labelers are made of 304 stainless steel and anodized aluminum. This extremely durable metal is specially treated to guard against rusting and other effects from harsher environments.
- Adjustable height applicator makes it easy to match production lines.

PRECISE

- The PP-601's stepper motor label position setting allows the operator to accurately set the label position, ensuring fast, accurate label delivery.
- The PP-601's controls are all in sync, making sure that all components run at the same speed.

COMPLIANT

- All Preferred Pack® labelers are manufactured in compliance with Good Manufacturing Practice (GMP) standards.
- On/Off switch and Emergency Stop Switch are prominently located on the main control panel.



Example of top label placement.

Dimensions L-W-H	36" x 29.5" x 62"
Dispensing Speed	80'/min (25m/min)
Maximum Label Size	5.1" W (130mm) x Infinite Length
Spool Diameter	14.5" (368mm)
Inner Core	3" (76mm)
Power	110 VAC, 60 HZ, 1 Phase, 700kW
Drive	Stepper Motor
Net Weight	150 lbs (68kg)